



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 015-003
Product name Disinfectant Spray for Health Care Use
Effective date 20-Mar-2013
Company information Claire Manufacturing Co.
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 1-630-543-7600
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 02-Sep-2011

2. Hazards Identification

Emergency overview Aerosol. FLAMMABLE
CONTENTS UNDER PRESSURE.
Will be easily ignited by heat, spark or flames. Contact with eyes may cause irritation.
Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Eye contact. Skin contact. Ingestion.

Eyes Moderately irritating to the eyes.

Skin Harmful if absorbed through the skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.
Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects Unconsciousness. Cyanosis (blue tissue condition, nails, lips, and/or skin). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Coughing. Jaundice. Defatting of the skin.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Ethyl Alcohol	64-17-5	40 - 50
n-Butane	106-97-8	15 - 20
Propane	74-98-6	5 - 8
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or Poison Control Center immediately.

Skin contact Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation Move to fresh air. Get medical attention if symptoms persist.

Ingestion In the unlikely event of swallowing contact a physician or poison control center.

Notes to physician

Keep victim under observation.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Foam. Dry chemical. Carbon dioxide (CO ₂).
Protection of firefighters	
Protective equipment and precautions for firefighters	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
Methods for cleaning up	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin.
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 2 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Do not get in eyes. Chemical goggles are recommended.
Skin protection	Chemical resistant gloves.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	143.6 °F (62.2 °C) estimated
Color	colorless
Density	0.7516 g/cm ³ estimated
Flammability (HOC)	23.3798 kJ/g estimated

Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	fruity alcoholic
pH	9.5 - 10.5
Physical state	Liquid.
Pressure	75 - 90 psig @ 70F
Solubility	Partially
Specific gravity	0.7517

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include oxides of nitrogen.

11. Toxicological Information

Acute effects Acute LC50: 83 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Ethyl Alcohol	64-17-5	Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization Not expected to be hazardous by OSHA criteria.

Carcinogenicity

IARC - Group 1 (Carcinogenic to Humans)

Ethyl Alcohol	64-17-5	Monograph 100E [2012] (in alcoholic beverages); Monograph 96 [2010] (in alcoholic beverages)
---------------	---------	--

Teratogenicity Animal experiments showed mutagenic and teratogenic effects.

12. Ecological Information

Ecotoxicity LC50 1750 mg/L, Fish, 96.00 Hours,
EC50 929 mg/L, Daphnia, 48.00 Hours,
Contains a substance which causes risk of hazardous effects to the environment.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructions Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
 Hazard class 2.1
 UN number 1950

Additional information:

Packaging exceptions LTD QTY
 Item 5F
 Labels required None
 Transport Category 2

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
 Hazard class 2.1
 UN number 1950

Additional information:

Packaging exceptions LTD QTY
 Labels required 2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. Pesticides are exempt from TSCA.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

U.S. - Pennsylvania - RTK (Right to Know) List

Ethyl Alcohol	64-17-5	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 3
Physical hazard: 0
Personal protection:

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

MSDS sections updated

Product and Company Identification: Product Review
Composition / Information on Ingredients: Ingredients
Hazards Identification: Target organs
Hazards Identification: Main symptoms

Prepared by

Regulatory Compliance



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 811-003
Product name **Multi-Surface Furniture Polish**
Effective date 10-Aug-2012
Company information Claire Manufacturing Co.
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 1-630-543-7600
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 01
Product use Furniture polish

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.
Potential health effects
Eyes Health injuries are not known or expected under normal use.
Skin Health injuries are not known or expected under normal use.
Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Ingestion Exposure by ingestion of an aerosol is unlikely.
Target organs Central nervous system.
Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.
Signs and symptoms Narcosis.

3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	1 - 3
Propane	74-98-6	1 - 3
Non-hazardous and other components below reportable levels		> 90

4. First Aid Measures

First aid procedures
Eye contact Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
Skin contact Rinse with water. Get medical attention if irritation develops and persists.
Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Ingestion In the unlikely event of swallowing contact a physician or poison control center.
Notes to physician Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media
Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Protection of firefighters
Protective equipment and precautions for firefighters In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid prolonged exposure.
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Not normally needed.
Skin protection	No special protective equipment required.
Respiratory protection	No personal respiratory protective equipment normally required. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Film.
Boiling point	188.6 °F (87.2 °C) estimated
Color	White.
Density	0.9667 g/cm3 estimated
Flammability (HOC)	4.2926 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) estimated
Form	Aerosol.
Freezing point	Not available
Odor	fruity
pH	10 - 11
Physical state	Liquid.
Pressure	65 - 85 psig @ 70F
Solubility	Completely
Specific gravity	0.9668 estimated

10. Chemical Stability & Reactivity Information

Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LC50: 3311 mg/l/4h estimated, Rat, Inhalation Acute LD50: 26282 mg/kg estimated, Rat, Dermal
---------------	---

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	LC50 3429 mg/L, Fish, 96.00 Hours, EC50 26718 mg/L, Daphnia, 48.00 Hours, Contains a substance which causes risk of hazardous effects to the environment.
-------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Aerosols
Hazard class	2.1
UN number	UN1950
Additional information:	
Special provisions	153, N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None



Further information	This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking but not concurrently.
---------------------	---

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA**Basic shipping requirements:**

Proper shipping name Aerosols, flammable
 Hazard class 2.1
 UN number 1950

Additional information:

Packaging exceptions LTD QTY
 Labels required 2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1
 Flammability: 2
 Physical hazard: 0
 Personal protection:

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by

Regulatory Compliance



SAFETY DATA SHEET

1. Identification

Product number 1000004842
Product identifier **STAINLESS STEEL POLISH & CLEANER (OIL BASE)**
Company information Claire Manufacturing Co.
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 1-630-543-7600
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 01
Recommended use CLEANER
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Serious eye damage/eye irritation Category 2A
Specific target organ toxicity, single exposure Category 3 narcotic effects
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
Hazardous to the aquatic environment, long-term hazard Category 3
OSHA defined hazards Not classified.
Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement
Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye/face protection.
Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	20 - 40
White Mineral Oil		8042-47-5	20 - 40
Acetone		67-64-1	10 - 20
Propane		74-98-6	10 - 20
Methyl Acetate		79-20-9	2.5 - 10
Fragrance		Proprietary	0.1 - 1
Odorless Mineral Spirits		64741-65-7	0.1 - 1
D-Alpha Tocopherol (Vitamin E)		59-02-9	0.01 - 0.1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3 200 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL TWA	750 ppm 500 ppm
Methyl Acetate (CAS 79-20-9)	STEL TWA	250 ppm 200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Methyl Acetate (CAS 79-20-9)	STEL TWA	760 mg/m3 250 ppm 610 mg/m3 200 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection	
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear.
Physical state	Gas.
Form	Aerosol.
Color	Light yellow.
Odor	Citrus
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	62.28 °F (16.82 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	2.5 % estimated
Flammability limit - upper (%)	12 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	45 - 65 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	488.23 °F (253.46 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.765 - 0.865 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates.
Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Not available.
Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.
Skin contact No adverse effects due to skin contact are expected.
Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg 2.2 ml/kg
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Methyl Acetate (CAS 79-20-9)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC100	Rabbit	98.4 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	6482 mg/kg

Components	Species	Test Results
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52 %, 120 Minutes 1355 mg/l 658 mg/l/4h
White Mineral Oil (CAS 8042-47-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	2.18 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	5000.0001 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product	Species	Test Results
STAINLESS STEEL POLISH & CLEANER (OIL BASE) (CAS Mixture)		
Aquatic		
Algae	IC50	Algae 1283.3676 mg/L, 72 Hours estimated
Crustacea	EC50	Daphnia 8543.2627 mg/L, 48 Hours estimated
Fish	LC50	Fish 8.2044 mg/L, 96 Hours estimated
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours

Components	Species		Test Results
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Methyl Acetate (CAS 79-20-9)			
Aquatic			
Algae	IC50	Algae	120.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1026.7 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
Odorless Mineral Spirits (CAS 64741-65-7)			
Aquatic			
Algae	IC50	Algae	30000 mg/L, 72 Hours
White Mineral Oil (CAS 8042-47-5)			
Aquatic			
Fish	LC50	Fish	10000.0001, 96 Hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Methyl Acetate	0.18
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82

Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950
UN proper shipping name Aerosols, flammable
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Label(s) 2.1
Packing group Not applicable.
Environmental hazards No.
ERG Code 10L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed.
Cargo aircraft only Allowed.
Packaging Exceptions LTD QTY

IMDG

UN number UN1950
UN proper shipping name AEROSOLS
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Label(s) 2.1
Packing group Not applicable.
Environmental hazards
Marine pollutant No.
EmS F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)

6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)

35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)

6532

US state regulations

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Methyl Acetate (CAS 79-20-9)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Methyl Acetate (CAS 79-20-9)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Methyl Acetate (CAS 79-20-9)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-19-2015

Version # 01


Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

ECONOMICAL JANITORIAL & PAPER SUPPLIES, INC.
 1420-F SAMS AVE. HARAHAN, LA 70123 (504) 464-7166

Date: MAY 20, 2008

EMERGENCY PHONE NUMBER
 (800) -- 535-5053 INFOTRAC



SECTION: I TRADE NAME : ORANGE BIO FRESH
 IDENTIFICATION CHEMICAL FAMILY : BACTERIAL ENZYME COMPLEX
 OF PRODUCT PRODUCT NUMBER : 5282
 SHIPPING DESCRIPTION: CLEANING COMPOUND, NOS

SECTION: II - HAZARDOUS INGREDIENTS
 HAZARDOUS COMPONENTS OSHA PEL ACGIH TLV CAS #

ALL COMPONENTS APPEAR ON THE TSCA INVENTORY.
 COMPONENTS NOT LISTED ARE EITHER NON HAZARDOUS
 OR IN CONCENTRATIONS OF LESS THAN 1%

SECTION 313 - SUPPLIER NOTIFICATION:

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372
 *** CAS #*** CHEMICAL NAME % By Wt.

NONE

THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS:

TRANS GULF FUEL

BOILING POINT = >212 DEGREES F
 SPECIFIC GRAVITY (H2O=1) = 1.00
 SOLUBILITY IN WATER = COMPLETE
 APPEARANCE = LIGHT ORANGE LIQUID
 ODOR = ORANGE ODOR
 VAPOR PRESSURE (mmHg) = N/A
 VAPOR DENSITY (AIR=1) = N/A
 EVAPORATION RATE (Bubyl Act=1) = N/A
 POUNDS PER GALLON = 8.33

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

FLASH POINT = NONE
 EXTINGUISHING MEDIA = AS REQUIRED BY SURROUNDING FIRE
 SPECIAL FIRE FIGHTING = WEAR SELF-CONTAINED FULL-FACE
 PROCEDURES = BREATHING APPARATUS
 UNUSUAL HAZARDS = NONE KNOWN

SECTION V - REACTIVITY DATA:

STABILITY = STABLE
 CONDITIONS TO AVOID = EXTREME TEMPERATURES
 POLYMERIZATION = WILL NOT OCCUR
 CONDITIONS TO AVOID = NONE
 INCOMPATIBLE MATERIALS = STRONG ACIDS AND OXIDIZERS
 HAZARDOUS DECOMPOSITION OR BY-PRODUCTS = CO, CO2

SECTION VI - HEALTH HAZARDS DATA:

THRESHOLD LIMIT VALUE = NOT ESTABLISHED
 CARCINOGENICITY =
 NTP = NO
 IARC MONOGRAPHS = NO
 OSHA REGULATED = NO
 HEALTH HAZARDS ACUTE/CHRONIC = EYES: MAY CAUSE REDNESS AND IRRITATION TO EYES, NAUSEA, VOMITING AND DIARRHEA MAY OCCUR UPON INGESTION. PROLONGED SKIN CONTACT MAY CAUSE MILD IRRITATION.
 EMERGENCY FIRST AID PROCEDURES =
 INHALATION = MOVE TO FRESH AIR. CONSULT PHYSICIAN IF SYMPTOMS PERSIST.
 INGESTION = GIVE LARGE QUANTITIES OF WATER THEN SEVERAL GLASSES OF MILK.
 INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.
 EYE CONTACT = FLUSH EYES IMMEDIATELY WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES. LIFTING EYELIDS OCCASIONALLY.
 GET MEDICAL ATTENTION.
 SKIN CONTACT = REMOVE CONTAMINATED CLOTHING RINSE SKIN THOROUGHLY WITH SOAP AND WATER.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING:

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
 LARGE SPILLS: CONTAIN SPILL AND PUMP TO RECOVER
 SMALL SPILLS: SPILL CAN BE MOPPED UP THEN FLUSH CONTAMINATED AREA WITH PLENTY OF WATER.
 WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.
 PRECAUTIONS TO TAKE IN HANDLING & STORAGE: STORE IN COOL, DRY PLACE KEEP CONTAINER CLOSED WHEN NOT IN USE.
 OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - CONTROL MEASURES:

RESPIRATORY PROTECTION = NONE REQUIRED
 VENTILATION = USE ADEQUATE VENTILATION
 PROTECTIVE GLOVES = NONE REQUIRED
 EYE PROTECTION = RECOMMENDED
 OTHER PROTECTIVE MEASURES = RINSE HANDS THOROUGHLY AFTER USE.

MANUFACTURER:

TRANS GULF INDUSTRIES, INC. EMERGENCY PHONE #
 6101 HUMBREYS STREET DAY M-F (504) - 733-7865
 PO BOX 23809 NIGHT (800) - 535-5053
 HARAHAN, LA 70183


This information is drawn from recognized sources believed to be reliable. TRANS GULF INDUSTRIES, INC. makes no guarantee or assurance as to the accuracy of this information. The user should be aware of changing technology, research, regulations and analytical procedures that may require changes herein. The above data is supplied upon the condition that customers will evaluate this information and then determine its suitability for their use. Only USA Regulations apply to the above.

MATERIAL SAFETY DATA SHEET

ECONOMICAL JANITORIAL & PAPER SUPPLIES, INC.
 1420-F SAMS AVE. HARAHAN, LA 70123 (504) 464-7166

Date: JANUARY 1, 2013

EMERGENCY PHONE NUMBER
 (800) -- 535-5053 INFOTRAC



SECTION I - TRADE NAME : SPOTLESS ALL PURPOSE CLEANER
IDENTIFICATION CHEMICAL FAMILY : CLEANER
PRODUCT NUMBER : 5334
SHIPPING DESCRIPTION: CLEANING COMPOUND, NOS

SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	OSHA PEL	ACGIH	TLV	CAS #
NONE				

SECTION 313 - SUPPLIER NOTIFICATION:
 THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372.
 CAS #*
 CHEMICAL NAME % By Wt.
 NONE

THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

SECTION III - PHYSICAL/CHEMICAL

CHARACTERISTICS:
 BOILING POINT= >212 DEGREES F
 SPECIFIC GRAVITY (428=1)= 1.000
 SOLUBILITY IN WATER= COMPLETE
 APPEARANCE= YELLOW
 COLOR= LEMON
 VAPOR PRESSURE (mmHg)= N/A
 VAPOR DENSITY (Air=1)= N/A
 EVAPORATION RATE (Buyl/Air=1) = N/A
 POUNDS PER GALLON= 8.337

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:
 FLASH POINT= NONE
 EXTINGUISHING MEDIA= AS REQUIRED BY SURROUNDING FIRE
 SPECIAL FIRE FIGHTING= WEAR NIOSH/MSHA APPROVED SELF-CONTAINED FULL-FACE BREATHING APPARATUS
 UNUSUAL HAZARDS= PRODUCTS OF COMBUSTION ARE TOXIC.

SECTION V - REACTIVITY DATA:
 STABILITY= STABLE
 CONDITIONS TO AVOID= EXTREME TEMPERATURES
 POLYMERIZATION= WILL NOT OCCUR
 CONDITIONS TO AVOID= NONE
 COMPATIBLE MATERIALS= STRONG ACIDS AND OXIDIZERS
 HAZARDOUS DECOMPOSITION OR BY-PRODUCTS= CO, CO.

SECTION VI - HEALTH HAZARDS DATA:
 THRESHOLD LIMIT VALUE= NOT ESTABLISHED
 CARCINOGENICITY= NTP= NO
 IARC MONOGRAPHS= NO
 OSHA REGULATED= NO
 HEALTH HAZARDS ACUTE/CHRONIC= NO
 IRRITATION AND POSSIBLE TISSUE DAMAGE DEPENDING ON EXPOSURE, NAUSEA, VOMITING AND DIARRHEA MAY OCCUR UPON INGESTION. PROLONGED SKIN CONTACT MAY CAUSE MILD TO NO IRRITATION, DEFTATING AND DERMATITIS.
 EMERGENCY FIRST AID PROCEDURES =
 INHALATION = MOVE TO FRESH AIR. CONSULT PHYSICIAN IF SYMPTOMS PERSIST.
 IF SYMPTOMS PERSIST, GIVE LARGE QUANTITIES OF MILK.
 INGESTION = THEN SEVERAL GLASSES OF WATER. DO NOT INDUCE VOMITING.
 GET MEDICAL ATTENTION IMMEDIATELY.
 EYE CONTACT = FLUSH EYES IMMEDIATELY WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES, LIFTING EYELIDS OCCASIONALLY.
 GET MEDICAL ATTENTION.
 SKIN CONTACT = REMOVE CONTAMINATED CLOTHING.
 RINSE SKIN THOROUGHLY WITH SOAP AND WATER.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING:
 STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
 LARGE SPILLS: CONTAIN SPILL AND PUMP TO RECOVER
 SMALL SPILLS: SPILL CAN BE MOPPED UP THEN FLUSH CONTAMINATED AREA WITH PLENTY OF WATER.
 WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.
 PRECAUTIONS TO TAKE IN HANDLING & STORAGE: STORE IN COOL, DRY PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE.
 OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - CONTROL MEASURES:
 RESPIRATORY PROTECTION= NONE REQUIRED WITH ADEQUATE VENTING
 VENTILATION= USE ADEQUATE CROSS VENTILATION
 PROTECTIVE GLOVES= RECOMMENDED
 EYE PROTECTION= RECOMMENDED
 OTHER PROTECTIVE MEASURES= WASH HANDS THOROUGHLY AFTER USE.

MANUFACTURER: TRANS GULF INDUSTRIES, INC.
 6101 GUMPHREYS STREET
 PO BOX 23809
 HARAHAN, LA 70183


EMERGENCY PHONE #
 DAY M-F (504) - 733-7865
 NIGHT (800) - 535-5053

This information is drawn from recognized sources believed to be reliable. TRANS GULF INDUSTRIES, INC. makes no guarantees or assumes any liability in connection with this information. The user should be aware of changing technology, research, regulations and analytical procedures that may require changes herein. The above data is supplied upon the condition that customers will evaluate this information and then determine its suitability for their use. Only USA Regulations apply to the above.

MATERIAL SAFETY DATA SHEET

ECONOMICAL JANITORIAL & PAPER SUPPLIES, INC.
 1420-F SAMS AVENUE, HARRAHAN, LA 70123 (504) 464-7166 Date: FEBRUARY 25, 2013

EMERGENCY PHONE NUMBER
 (800) - 535-5053 INFOTRAC



SECTION I - TRADE NAME : Institutional Floor Cleaner
 IDENTIFICATION CHEMICAL FAMILY : Cleaning Compound
 OF PRODUCT : PRODUCT NUMBER : 5400
 SHIPPING DESCRIPTION: CLEANING COMPOUND, NOS

SECTION II - HAZARDOUS INGREDIENTS
 ZARDOUS COMPONENTS OSHA PEL ACCIH TLV CAS #

SODIUM METASILICATE NE NE 6834-92-0
 SODIUM HYDROXIDE NE NE 1310-73-2

SECTION 313 - SUPPLIER NOTIFICATION:

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372.
 CAS # CHEMICAL NAME % By Wt.

1310-73-2 SODIUM HYDROXIDE >5%

THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS:

BOILING POINT= >212 DEGREES F
 SPECIFIC GRAVITY (H28=1)= 1
 SOLUBILITY IN WATER= COMPLETE
 APPEARANCE= CLEAR YELLOW LIQUID
 COLOR= MILD
 VAPOR PRESSURE (mmHg)= N.E.
 VAPOR DENSITY (Air=1)= N.E.
 AUTOFLAMMABILITY (Bulb) (Acf=1) = N.E.
 UNDS PER GALLON= 8.34

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

FLASH POINT= NONE
 EXTINGUISHING MEDIA= AS REQUIRED BY SURROUNDING FIRE
 SOCIAL FIRE FIGHTING= WEAR SELF-CONTAINED FULL-FACE
 PROCEDURES= BREATHING APPARATUS
 USUAL HAZARDS= DILUTION WITH H2O MAY RELEASE HEAT

SECTION V - REACTIVITY DATA:

ABILITY= STABLE
 CONDITIONS TO AVOID= EXTREME TEMPERATURES
 LYMERIZATION= WILL NOT OCCUR
 CONDITIONS TO AVOID= NONE
 COMPATIBLE MATERIALS= STRONG ACIDS AND OXIDIZERS
 ZARDOUS DECOMPOSITION OR BY-PRODUCTS= CO2, CO.

SECTION VI - HEALTH HAZARDS DATA:

THRESHOLD LIMIT VALUE= NOT ESTABLISHED
 CARCINOGENICITY= NOT ESTABLISHED
 NTP= NO
 IARC MONOGRAPHS= NO
 OSHA REGULATED= NO
 HEALTH HAZARDS: ACUTE/CHRONIC = EYES: MODERATE TO SEVERE
 IRRITATION AND POSSIBLE TISSUE DAMAGE DEPENDING ON EXPOSURE. NAUSEA,
 VOMITING AND DIARRHEA MAY OCCUR UPON INGESTION. PROLONGED SKIN
 CONTACT MAY CAUSE MODERATE IRRITATION, DEPARTING AND DERMATITIS.
 EMERGENCY FIRST AID PROCEDURES =
 INHALATION = MOVE TO FRESH AIR. CONSULT PHYSICIAN
 IF SYMPTOMS PERSIST.
 GIVE LARGE QUANTITIES OF WATER
 INGESTION = THEN SEVERAL GLASSES OF WATER
 DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.
 EYE CONTACT = FLUSH EYES IMMEDIATELY WITH LARGE QUANTITIES OF
 WATER FOR 15 MINUTES, LIFTING EYELIDS OCCASIONALLY.
 SKIN CONTACT = GET MEDICAL ATTENTION.
 REMOVE CONTAMINATED CLOTHING IMMEDIATELY
 WASH SKIN THOROUGHLY WITH SOAP AND WATER. MEDICAL ATTENTION!

SECTION VII - PRECAUTIONS FOR SAFE HANDLING:

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
 LARGE SPILLS: CONTAIN SPILL AND PUMP TO RECOVER
 SMALL SPILLS: SPILL CAN BE MOPPED UP THEN FLUSH CONTAMINATED
 AREA WITH PLENTY OF WATER. THEN NEUTRALIZE
 WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE
 WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.
 PRECAUTIONS TO TAKE IN HANDLING & STORAGE: STORE IN COOL, DRY PLACE
 KEEP CONTAINER CLOSED WHEN NOT IN USE.
 OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - CONTROL MEASURES:

RESPIRATORY PROTECTION= NONE REQUIRED WITH ADEQUATE VENTING
 VENTILATION= USE ADEQUATE CROSS VENTILATION
 PROTECTIVE GLOVES= RUBBER GLOVES
 EYE PROTECTION= SAFETY GOGGLES
 OTHER PROTECTIVE MEASURES= WASH HANDS THOROUGHLY AFTER USE.

MANUFACTURER:

TRANS GULF INDUSTRIES, INC.
 6101 HUMPHREYS STREET
 PO BOX 23809
 HARRAHAN, LA 70183
 EMERGENCY PHONE #
 DAY M-F (504) - 733-7865
 NIGHT (800) - 535-5053

This information is drawn from recognized sources believed to be reliable. TRANS GULF INDUSTRIES INC. makes no guarantees or assurances of changing technology, research, regulations and analytical procedures that may require changes herein. The above data is supplied upon the condition that customers will evaluate this information and then determine its suitability for their use. Only USA Regulations apply to the above.


MATERIAL SAFETY DATA SHEET

ECONOMICAL JANITORIAL & PAPER SUPPLIES, INC.
 1420-F SAMS AVE. HARAHAN, LA 70123 (504) 464-7166

Date: MAY 22, 2008

(800) -- 535-5053 INFOTRAC

EMERGENCY PHONE NUMBER



SECTION: 1 TRADE NAME : MINT DEODORANT CLEANER
 IDENTIFICATION CHEMICAL FAMILY : CLEANER
 OF PRODUCT : PRODUCT NUMBER : 305984
 SHIPPING DESCRIPTION: CLEANING COMPOUND, NOS

SECTION: II - HAZARDOUS INGREDIENTS
 HAZARDOUS COMPONENTS OSHA PEL ACCOIH TLY CAS #
 NONE

SECTION 313 - SUPPLIER NOTIFICATION:
 THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 312.
 CAS # CHEMICAL NAME % By Wt.
 NONE

THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS:
 BOILING POINT= >212 DEGREES F
 SPECIFIC GRAVITY (H2O=1)= 1.000
 SOLUBILITY IN WATER= COMPLETE
 APPEARANCE= CLEAR GREEN
 DOR= MINT
 VAPOR PRESSURE (mmHg)= N/A
 VAPOR DENSITY (Air=1)= N/A
 VAPORIZATION RATE (Boyl Act=1)= N/A
 POUNDS PER GALLON= 8.337

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:
 FLASH POINT= NONE
 EXTINGUISHING MEDIA= AS REQUIRED BY SURROUNDING FIRE
 SPECIAL FIRE FIGHTING= WEAR SELF-CONTAINED FULL-FACE
 PROCEDURES= BREATHING APPARATUS
 UNUSUAL HAZARDS= NONE KNOWN

SECTION V - REACTIVITY DATA:
 STABILITY= STABLE
 CONDITIONS TO AVOID= EXTREME TEMPERATURES
 POLYMERIZATION= WILL NOT OCCUR
 CONDITIONS TO AVOID= NONE
 INCOMPATIBLE MATERIALS= STRONG ACIDS AND OXIDIZERS
 HAZARDOUS DECOMPOSITION OR BY-PRODUCTS= CO, CO2

This information is drawn from recognized sources believed to be reliable. TRANS GULF INDUSTRIES, INC. makes no guarantee or assumes any liability in connection with this information. The user should be aware of changing technology, research, regulations and analytical procedures that may require changes herein. The above data is supplied upon the condition that customers will evaluate this information and then determine its suitability for their use. Only USA Regulations apply for the above.

SECTION VI - HEALTH HAZARDS DATA:
 THRESHOLD LIMIT VALUE= NOT ESTABLISHED
 CARCINOGENICITY= NOT ESTABLISHED
 NTP= NO
 IARC MONOGRAPHS= NO
 OSHA REGULATED= NO
 HEALTH HAZARDS ACUTE/CHRONIC = EYES: MODERATE TO SEVERE IRRITATION AND POSSIBLE TISSUE DAMAGE DEPENDING ON EXPOSURE. NAUSEA, VOMITING AND DIARRHEA MAY OCCUR UPON INGESTION. PROLONGED SKIN CONTACT MAY CAUSE MODERATE IRRITATION, DEPARTING AND DERMATITIS.
 EMERGENCY FIRST AID PROCEDURES =
 INHALATION = MOVE TO FRESH AIR. CONSULT PHYSICIAN IF SYMPTOMS PERSIST.
 INGESTION = GIVE LARGE QUANTITIES OF WATER THEN SEVERAL GLASSES OF MILK.
 EYE CONTACT = GET MEDICAL ATTENTION IMMEDIATELY. FLUSH EYES IMMEDIATELY WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES, LIFTING EYELIDS OCCASIONALLY.
 GET MEDICAL ATTENTION.
 SKIN CONTACT = REMOVE CONTAMINATED CLOTHING. RINSE SKIN THOROUGHLY WITH SOAP AND WATER.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING:
 STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
 LARGE SPILLS: CONTAIN SPILL AND PUMP TO RECOVER
 SMALL SPILLS: SPILL CAN BE MOPPED UP THEN FLUSH CONTAMINATED AREA WITH PLENTY OF WATER.
 WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.
 PRECAUTIONS TO TAKE IN HANDLING & STORAGE: STORE IN COOL, DRY PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE.
 OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - CONTROL MEASURES:
 RESPIRATORY PROTECTION= NONE REQUIRED WITH ADEQUATE VENTING
 VENTILATION= USE ADEQUATE CROSS VENTILATION
 PROTECTIVE GLOVES= RECOMMENDED
 EYE PROTECTION= RECOMMENDED
 OTHER PROTECTIVE MEASURES= WASH HANDS THOROUGHLY AFTER USE.

MANUFACTURER: TRANS GULF INDUSTRIES, INC.
 6101 HUMPHREYS STREET
 PO BOX 23809
 HARAHAN, LA 70183
 EMERGENCY PHONE #
 DAY M-F (504) - 733-7865
 NIGHT (800) - 535-5053



Complete Floor Finish

Version Number: 2

Preparation date: 2014-10-21

1. IDENTIFICATION

Product name: Complete Floor Finish
Product Code: 04649, 5104773, 04657
SDS #: MS0800471
Recommended use:

- Industrial/Institutional
- Floor finish for professional use

Uses advised against: Uses other than those identified are not recommended

Manufacturer, importer, supplier:
 US Headquarters
 Diversey, Inc.
 8310 16th St.
 Sturtevant, Wisconsin 53177-1964
 Phone: 1-888-352-2249
 MSDS Internet Address: www.diversey.com

Canadian Headquarters
 Diversey, Inc. - Canada
 3755 Laird Road
 Mississauga, Ontario L5L 0B3
 Phone: 1-800-668-3131

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

This product is not classified as hazardous according to OSHA 29CFR 1910.1200 (HazCom 2012-GHS) and current Canadian Controlled Products Regulations (CPR).

Precautionary Statements

May be mildly irritating to eyes and skin. In case of contact, immediately flush with plenty of water. If irritation occurs and persists, get medical attention.

Health hazards not otherwise classified (HHNOC) - Not applicable

Physical hazards not otherwise classified (PHNOC) - Not applicable

Classification for the diluted product @ RTU

This product is intended to be used neat.

Precautionary Statements

See undiluted product information above.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

Ingredient(s)	CAS #	Weight %
Diethylene glycol monoethyl ether	111-90-0	1% - < 3%
Ethylene glycol	107-21-1	1% - < 3%

Tall oil fatty acid	61790-12-3	1% - < 3%
---------------------	------------	-----------

*Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES

Undiluted Product:

Eyes: In case of contact, immediately flush with plenty of water. If irritation occurs and persists, get medical attention.
Skin: In case of contact, immediately flush with plenty of water. If irritation occurs and persists, get medical attention.
Inhalation: No specific first aid measures are required.
Ingestion: Rinse mouth with water.

Most Important Symptoms/Effects: No information available.
Immediate medical attention and special treatment needed: Not applicable.
Aggravated Medical Conditions: None known.

Diluted Product:

This product is intended to be used neat.

Eyes: See undiluted product information above.
Skin: See undiluted product information above.
Inhalation: See undiluted product information above.
Ingestion: See undiluted product information above.

5. FIRE-FIGHTING MEASURES

Specific methods: No special methods required
Suitable extinguishing media: The product is not flammable. Extinguish fire using agent suitable for surrounding fire.
Specific hazards: None known.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Contaminated surfaces will be extremely slippery.
Environmental precautions and clean-up methods: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Wash thoroughly after handling. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.
Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.
Aerosol Level (if applicable) : Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS #	ACGIH	OSHA
Diethylene glycol monoethyl ether	111-90-0	-	-
Ethylene glycol	107-21-1	100 mg/m ³ (Ceiling)	-
Tall oil fatty acid	61790-12-3	-	-

Undiluted Product:

Engineering measures to reduce exposure:
 No special ventilation requirements General room ventilation is adequate

Personal Protective Equipment

Eye protection: No special requirements under normal use conditions.
Hand protection: No special requirements under normal use conditions.

Skin and body protection: No special requirements under normal use conditions.
Respiratory protection: No special requirements under normal use conditions.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

This product is intended to be used neat.

Personal Protective Equipment

Eye protection: No special requirements under normal use conditions.
Hand protection: No special requirements under normal use conditions.
Skin and body protection: No special requirements under normal use conditions.
Respiratory protection: No special requirements under normal use conditions.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liquid	Color: Opaque, Tan
Evaporation Rate: No information available	Odor: Ammonia
Odor threshold: No information available.	Boiling point/range: Not determined
Melting point/range: Not determined	Decomposition temperature: Not determined
Autoignition temperature: No information available	Solubility: Completely Soluble
Solubility in other solvents: No information available	Relative Density (relative to water): 1.02
Density: 8.51 lbs/gal 1.02 Kg/L	Vapor density: No information available
Bulk density: No information available	Vapor pressure: No information available.
Flash point: > 200 °F > 93.3 °C	Partition coefficient (n-octanol/water): No information available
Dilution Flash Point: > 200 °F > 93.3 °C	Viscosity: No information available
Elemental Phosphorus: 0.07 % by wt.	VOC: 0.16 % *
pH: 9.2	VOC % by wt. at use dilution: 0.16 % *
Dilution pH: 9.2 @ RTU	Flammability (Solid or Gas): Not applicable
Metal Corrosion: Not determined	
Explosion limits: - upper: Not determined - lower: Not determined	

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity: Not Applicable
Stability: The product is stable
Hazardous decomposition products: None reasonably foreseeable.
Materials to avoid: Do not mix with any other product or chemical unless specified in the use directions.
Conditions to avoid: Do not freeze.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Eye contact, Skin contact, Inhalation

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: May be mildly irritating to skin. Symptoms may include redness and/or transient discomfort.
Eye contact: May be mildly irritating to eyes. Symptoms may include redness, watering and/or transient discomfort.
Ingestion: No information available.
Inhalation: No information available.
Sensitization: No known effects.

Numerical measures of toxicity

ATE - Oral (mg/kg): >5000

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: This product, as sold, if discarded or disposed, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

Contaminated Packaging: Do not re-use empty containers.

RCRA Hazard Class (undiluted product): Not Regulated

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diverse.com/dot/>, for up to date shipping information.

DOT (Ground) Bill of Lading Description: BUFFING OR POLISHING COMPOUNDS

IMDG (Ocean) Bill of Lading Description: BUFFING OR POLISHING COMPOUNDS

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Modified Acrylic Polymer	Proprietary	-	-	-	-
Acrylic polymer	Proprietary	-	-	-	-
Diethylene glycol monoethyl ether	111-90-0	-	X	-	-
Ethylene glycol	107-21-1	X	X	X	X
Tall oil fatty acid	61790-12-3	-	-	-	-

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Diethylene glycol monoethyl ether	111-90-0	1% - < 3%			X
Ethylene glycol	107-21-1	1% - < 3%	5000		X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol monoethyl ether	X		
Ethylene glycol	X		

SARA 311/312 Hazard Categories

Immediate: -
Delayed: -
Fire: -
Reactivity: -
Sudden Release of Pressure: -

Canada

WHMIS hazard class: Non-controlled.

Ingredient(s)	CAS #	NPRI
Ethylene glycol	107-21-1	X

16. OTHER INFORMATION

NFPA (National Fire Protection Association)

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 1

Flammability 0

Instability 0

Version Number: 2

Preparation date: 2014-10-21

Reason for revision:

Not applicable

Prepared by:

NAPRAC

Additional advice:

- Does not contain an added fragrance
- This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.